



18Vx2 Rotary Hammer BL LXT

DHR280ZJ

28mm SDS-PLUS Cordless Combination Hammer powered by two 18V Li-ion batteries.



TECHNICAL SPECIFICATIONS

Battery Type	Lithium-ion
Body only machine	✓
Voltage	36 (18V x2) v
Max in concrete	28 mm
Max. in steel	13 mm
Max. in wood	32 mm
Max in concrete (TCT core)	54 mm
Max in concrete (Diamond core)	65 mm
Optimum Drilling Range	4 - 16 mm
Impact energy	2.8 J
Shank	SDS-PLUS
Blows per minute	0 - 5,000 bpm
Noise sound pressure	93 dB(A)
Noise sound power	104 dB(A)
Noise K factor	3 dB(A)
No Load Speed	0 - 980 rpm
Vibration K factor	1.5 m/sec ²
Vibration: Hammer Drilling	9.0 m/sec ²

USER BENEFITS

- Brushless motor
- Electric brake
- Variable speed control by trigger
- Constant speed control
- Forward / reverse rotation
- LED job light
- 3x Operating modes (RO/RH/HO)
- Torque limiter
- "Soft no load" function automatically reduces the motor speed during idling to suppress the vibration of the machine body.
- Anti vibration technology
- Powered by two 18V Li-ion batteries in series to supply energy to the powerful 36V DC motor drive system.

[Link to product - makitauk.com](https://www.makita.com)



RELATED PRODUCTS

(Recom

■ STANDARD ACCESSORIES

821552-6

MAKPAC CONNECTOR CASE (TYPE



■ OPTIONAL ACCESSORIES

199581-0

DX08 DUST EXTRACTION SYSTEM



■ OTHER