

Atlas Copco Portable Air compressors



XAS 37 Kd
XAS 47 Kd
XAS 67 Kd
XAS 87 Kd

The XAS 37-87 Kd range is your reliable and long-lasting partner for all rental applications.

Tough working environments require robust equipment. An impact-resistant Hardhat™ canopy protects your investment while you get the job done. And a Kubota engine ensures a reliable source of compressed air to drive your pneumatic tools including chipping and jackhammers, nut runners, grinders and rammers.

Ease of maintenance is guaranteed with the new design and spin-on oil separator. And with the outlets and controls all in one place, the range is really easy to operate. With a towing weight of less than 750 kg, any driver with a standard driving license can tow the XAS 37-87 Kd range behind a car, facilitating transport.

The results? More than enough air to drive one, two or three pneumatic tools at once, matched to the best fuel efficiency at both low and peak air demands.





More than 140 years of experience in a light and powerful package

Technical data

Type		XAS 37 Kd	XAS 47 Kd	XAS 67 Kd	XAS 87 Kd
Normal effective working pressure	bar	7	7	7	7
Actual free air delivery	m³/min	2.0	2.5	3.6	5
	l/s	33	42	60	83
Max. sound power level	dB(A)	98	98	98	98
Fuel tank capacity	l	32	32	40	40
Total weight full option - dry	kg	530	565	687	687
Total weight full option - wet	kg	550	585	740	740

Kubota engine					
Model		D905	V1505D1105T	V1505	V1505-T
Full load engine speed	rpm	3600	3000	2900	3000
Engine power at full load	kW	18.5	19.4	26.5	33

Dimensions (in mm)			
Box			
Length	mm	1963	1965
Width	mm	1342	1336
Height	mm	1032	1112
Adjustable towbar			
Length (min/max) ¹⁾	mm	2800 / 3038	3157 / 3513
Width	mm	1342	1336
Height	mm	1280	1340
Fixed towbar			
Length	mm	2603	3078
Width	mm	1342	1336
Height	mm	1280	1340

1) with ball coupling (Ø 50mm)

Features & options

- Canopy
 - HardHat™
- Undercarriage
 - Fixed towbar with brakes
 - Adjustable towbar without brakes
- Towbar support
 - Support leg
 - Jockey wheel
- Towing eye
 - AC / BNA / DIN / GB / ITA / NATO eye
 - Ball coupling Ø 50 mm
- Road signalization
 - Full road signalization with 13 pole connector
 - Bumper and reflectors
 - 13 pole to 7 pole adapter for road signalization
- Wheel chocks
- Spillage free frame
- Customer colors and/or labels