

LED WORKLIGHT 100

SA100



EYE-FRIENDLY LIGHT, ANYWHERE YOU NEED IT

Zone 1 & 2 certified SA LUMIN EX LED Worklights are designed with you, the user, in mind. Advanced LED technology is combined with exceptionally low cost of ownership to provide complete peace of mind.

Exceptional cable gland and socket protection further improves the reliability of this product. The SA LUMIN LED Worklight 100 is our compact version and is available in linkable and standard formats. It consumes less than 29 watts of power (at 110V) yet pumps out 2850 lumens of light.





BENEFITS

- ATEX and IECEx Certified for Zones 1 and 2 (gas), 21 and 22 (dust)
- INMETRO Certified
- High Power LED technology
- Light output 2850 lumens (180°)
- Lightweight and compact
- Low cost of ownership
- Linkable versions available
- Advanced diffuser system
- Enhanced cable gland & socket protection
- Tough and durable
- High light output
- Waterproof and dustproof
- Supplied with Adjustable Hanging Straps and Protective Film

- Exceptionally reliable
- T4 Temperature rating
- Vessel Entry Kit available

CORE PRODUCT INFORMATION

SA LUMIN EX LED Worklight 100, 24W 24VAC/DC, c/w ATX plug and braided cable Order Code: SA100A24ATX

42VAC/DC, c/w CEAG plug and braided cable Order Code: SA100A42CEA

110VAC Linkable, c/w CEAG plug & socket and braided cable Order Code: SA100C110CEA

230VAC Linkable, c/w CEAG plug & socket and braided cable Order Code: SA100C230CEA

SA LUMIN Worklight Plain Bracket Order Code: SAFB090

SA LUMIN Worklight Magnetic Bracket Order Code: SAFB100



0

SA LUMIN Worklight Antistatic Protective Film Order Code: SASP113

SA LUMIN Worklight Magnetic Swivel Bracket
Order Code: SAFB105

SA LUMIN Worklight Antistatic Protective Bag Order Code: SAPB100/50

SA LUMIN Worklight Tripod Stand Order Code: SAFB150



SPECIFICATIONS

CERTIFICATION

⟨E⊋ II 2 GD Ex eb mb op is IIC T4 Gb Ex tb op is IIIC T80°C Db

INGRESS PROTECTION

VOLTAGE OPTIONS 12VAC/DC, 24VAC/DC, 42VAC/DC, 110VAC/DC, 230VAC/DC

PLUG/SOCKET OPTIONS

ATX CFAG & STAHL

OPERATING TEMPERATURE

-20°C to +55°C

LED LIFE

Approx. 50,000 hours

LIGHT OUTPUT

2850 lumens (180°)

LIGHT SOURCE High Power LED Module

CABLE LENGTH 5m (Linkable) 10m (Non-Linkable)

20m (Non-Linkable 24V)

(or as required) DIMENSIONS

675mm x 175mmØ

WEIGHT

1.8kg

24V



All SA LUMIN Worklights are supplied with anti-static Protective Film and adjustable Hanging Straps. ATX and STAHL connectors and different cable lengths also available - please contact SA Equip for more details.

























