

We call it 'Non-Powered, Powered Access'

As part of the Eco range the EcoLift still harnesses the same Eco friendly revolutionary 'Patented Stored Power System' as the PecoLift but at 4.20 m offers almost a metre extra in working height.

With no batteries (to charge and look after) and no hydraulic oil, the EcoLift is truly an Eco friendly solution.

Typical applications and uses:

1st & 2nd Fix. Pipe Work, M & E. FM.
Cleaning. Painting. Retail. Point of Sale. FM.

Key Features

- Intuitive to operate - turn handle to elevate
- Patented* lift mechanism, no power required
- Lightweight, easy to manoeuvre
- Small foot print (1.28 m x 0.70 m)
- Unlimited lift cycles, can be used 24/7
- Robust design for years of trouble free service
- Minimal operational costs, virtually maintenance free

PUSH AROUND - Self Powered

Indoor Use

Working Height: 4.20 m

Applications: 1st & 2nd fix.
Pipe Work, M&E. F.M. Cleaning.
Painting. Point of Sale. Retail.



Model ECOLIFT

LOW-LEVEL ACCESS

Specifications

WORKING DIMENSIONS

Maximum working height:	4.20 m
Maximum platform height:	2.20 m
Basket dimensions:	0.85 m (L) x 0.64 m (W)
Working foot print:	1.28 m x 0.70 m
Safe working load - platform:	150 kg (1 person + tools)
Maximum manual force:	200N
Maximum gradient for operation:	0 degrees
Maximum wind force:	Internal use only 0 m/s
Maximum castor point load:	234 kg (2.29kN)
Maximum wheel force:	234 kg
Power Sound Level:	less then 70DbA

CLOSED DIMENSIONS

Length:	1.28 m
Width:	0.70 m
Height:	1.94 m
Weight:	305 kg

LIFT CYCLES Unlimited

Safety features

- 'Auto-lok' brake on elevation
- Elevates only when operated
- Lifting mechanism interlocked



IMPORTANT

JLG is continually researching and developing products and reserves the right to make modifications without prior notice. All data in this document is indicative. Certain options or country standards will increase weight. Specifications may change to meet country standards or with the addition of optional equipment.

Due to continuous product improvements, JLG Industries reserves the right to make specification and/or equipment changes without prior notification.



JLG EMEA BV

Polaris Avenue 63
2132 JH Hoofddorp
The Netherlands
Phone: +31 (0)23 565 5665
www.jlg.com

An Oshkosh Corporation Company