



max. 150 kg/330 lbs



UM-VS-S/SE - complete version

UNIMOBIL UM-VS Laying Dolly

Basic version (without suction plate) equipped with SPEEDY VS-140/200 electrical operation 230 V or 110 V.

The UNIMOBIL UM-VS-140 is the perfect vacuum laying system for porous slabs and stone.

If you are already using a Speedy VS-140/200 please ask us for a quotation to upgrade it to a UM-VS! Available with integrated generator, unlimited operating range, more flexible!

The following components are required for a complete device: UM-VS-140/200 + SPEEDY VS-140/200 (230V) + SE-H Honda generator and pendular suspension for generator (see accessories).

- Advantage: Gentle and close positioning of slabs possible. Re-pick up possible. Also suitable for very porous stones.
- It is equipped with a 90° turnable suspension for the perfect positioning of the slabs.
- Including additional handle on the suction plate for better positioning of the laying material.
- Releasing of the suction force very simple by pulling a lever.
- Quick adjustment of the arm in 5 different positions.
- Durable surface protection by galvanizing.

Type	Description	Dimensions L x W mm (in)	Type of Drive electric/ AC (50 Hz) kW	Type of Drive electric/ AC (60 Hz) kW	Electric Voltage / AC (50 Hz) V	Electric Voltage / AC (60 Hz) V	Dead Weight kg (lbs)	Working Load Limit/WLL kg (lbs)	Working Load Limit/WLL -200 mbar kg (lbs)	Order-Number
UM-VS-140/200	Basic version for installing the SPEEDY VS-140/200						45 (99)	150 (331)		42740017
VS-140/200	incl. suction plate 50 kg (110 lbs)	300 x 250 (11.81 x 9.84)	1.5		230		24 (53)		200 (441)	52700015
VS-140/200-110	incl. suction plate 50 kg (110 lbs)	300 x 250 (11.81 x 9.84)		1.5		110	24 (53)		200 (441)	52700019

Accessories:

Type	Description	Dimensions oval, L x B mm (in)	Dimensions L x W mm (in)	Type of Drive Petrol Engine kW	Electric Voltage /AC (50 Hz) V	Dead Weight kg (lbs)	Working Load Limit/WLL -200 mbar kg (lbs)	Order-Number
SE-H Generator Honda EU 22 i	230 V 50 Hz petrol engine			2.25	230	22.5 (50)		52500243
Swinging Suspension UM	for Honda generator					1.1 (2.43)		42720238
VS-SPS-50-30/ 25	Suction Plate		300 x 250 (11.81 x 9.84)			1.44 (3.17)	50 (110)	42710013
VS-GH-SPS-80- 40/30	Suction Plate		400 x 300 (15.74 x 11.81)			2.1 (4.63)	80 (176)	42710129
VS-GH-SPS-100- 50/30	Suction Plate		500 x 300 (19.69 x 11.81)			2.7 (5.95)	100 (220)	42710130
VS-GH-SPS-140- 70/30	Suction Plate		700 x 300 (27.56 x 11.81)			3.4 (7.50)	140 (309)	42710131